
# **Pop Rivet**

### **Aluminum**





#### Material:

Head made out of Aluminum, Pin made out of Galvanized Steel.

### **Description and Typical application:**

Pop Rivets are designed to secure two or more layers of Metal Jacketing, Banding, Straps, etc.

### Application:

Insert Pop Rivet in drilled / punched hole and fasten with adequate rivet gun.

# PHYSICAL PROPERTIES:

TEMPERATURE LIMITS : 350 oC

Combustibility : Non combustible - DIN 4102

# STANDARD SIZES

 $\begin{array}{ll} \mbox{Diameter (d)} & : 3.2 \mbox{ mm} \\ \mbox{Length (L)} & : 6.0\text{-}18.0 \mbox{ mm} \end{array}$ 

 $\begin{array}{ll} \mbox{Diameter (d)} & : 4.0 \mbox{ mm} \\ \mbox{Length (L)} & : 6.0\text{-}18.0 \mbox{ mm} \end{array}$ 

 $\begin{array}{ll} \mbox{Diameter (d)} & : 4.8 \mbox{ mm} \\ \mbox{Length (L)} & : 9.0\text{-}18.0 \mbox{ mm} \end{array}$ 

Other sizes on request, as per market availability.

# SUPPLY UNITS / PACKING

 Dia 3.2 mm
 : 1000 pcs/carton

 Dia 4.0 mm
 : 500 pcs/carton

 Dia 4.8 mm
 : 500 pcs/carton

Other packings possibility on request

#### **DISCLAIMER**

The information in this data sheet is given to the best of our knowledge based on actual tests and is believed to be typical for the product.

No guarantee of results is implied, however, since conditions of use are beyond our control.

We reserve the right to change the given data without prior notice.

Page 1 of 1

PRODUCT I N F O

INSULATION PRODUCTS