


Stainless Steel Screws

Self-tapping
(with optional Neoprene Washer)



Material :

Stainless Steel A2, according to DIN 17 440 & DIN 267 (type 302 or 304).

Description and Typical application:

Self-tapping stainless screws are used to secure all kind of weather-protection metal jacketing such as aluminum, stainless steel, pre-coated sheet metal and the like.

Application:

Drill holes of smaller diameter than the screw (+/- 1mm) at the required locations.
Insert the screw tip and use adequate screwdriver (manual or mechanical) until the screw head comes into contact with the metal jacket.
Do not overtight or force the screw into position.

PHYSICAL PROPERTIES:

TEMPERATURE LIMITS : 500 oC (screw), 100 oC (washer)
Combustibility : B1 - DIN 4102 (washer only)

STANDARD SIZES

Diameter (d) : 4.0 mm
Length (L) : 16.0 mm

NOTES:

According to DIN 18 421, the use of washers is mandatory for aluminum, stainless steel and coated sheet metal jacketing.

Other sizes on request, as per market availability.

SUPPLY UNITS / PACKING

Dia 4.0 mm : 1000 pcs/carton
(+/- 1.5 Kg/carton)

Other packings possibility on request

DISCLAIMER

The information in this data sheet is given to the best of our knowledge based on actual tests and is believed to be typical for the product.

No guarantee of results is implied, however, since conditions of use are beyond our control.

We reserve the right to change the given data without prior notice.