



Thermal Insulation Products - Screws & Rivets

Self Tapping Screws

DIN 7971

Self Tapping Screws Pan Head Slotted. Diameter 2.2-6.3mm



DIN 7972 Self Tapping Screws Countersunk Slotted. Diameter 2.2-6.3mm



DIN 7973

Self Tapping Screws Domehead Countersunk Slotted. Diameter 2.2-6.3mm



DIN 7976 Self Tapping Screws Hexagonal Head. Diameter 2.2-8.0mm



DIN 7981

Self Tapping Screws Domehead Phillips. Diameter 2.2-6.3mm



DIN 7982 Self Tapping Screws Countersunk Phillips. Diameter 2.2-6.3mm

DIN 7983 Self Tapping Screws Domehead Countersunk Phillips. Diameter 2.2-6.3mm

JENEN S

Type A diameter -/

Available in: Stainless Steel Zinc Plated Aluminium

Type A/B diameter -

APPING SCREWS - DIN 7971 PANHEAD SLOTTED & DIN 7981 PANHEAD POZI DIAMETER NO 4 NO 6 NO 8 NO 10 NO 12 NO 14 INCH MM 2.9 3.5 4.2 4.8 5.5 6.3 1/4" 6.5 V V - - - 3/8" 9.5 V V V - - 1/2" 13 V V V - - 5/8" 16 V V V V - 3/4" 19 V V V V - 1" 25 V V V V - 1 1/4" 32 V V V - - 1 1/4" 32 V V V V - - 1 1/2" 38 V V V V - - 1 3/4" 45 - V V V - - 2" 50 V V V -									
$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$		LENGTH	NO 4	NO 6	NO 8	NO 10	NO 12	NO 14	
$ \begin{array}{c c c c c c c c c c c c c c c c c c c $	1/4"	6.5	 ✓ 	 ✓ 					1
$ \begin{array}{c c c c c c c c c c c c c c c c c c c $	3/8"	9.5	 ✓ 	 ✓ 	 ✓ 	 ✓ 			1
$ \begin{array}{c c c c c c c c c c c c c c c c c c c $	1/2"	13	 ✓ 						
7/8" 22 ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ <td>5/8"</td> <td>16</td> <td> ✓ </td> <td></td> <td></td>	5/8"	16	 ✓ 						
1" 25 V V V V V V V Image: constraint of the state	3/4"	19	 ✓ 						
1 1/4" 32 V V V V V V Image: Constraint of the state o	7/8"	22		 ✓ 	 ✓ 	 ✓ 	 ✓ 		
1 1/2" 38 ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ </td <td>1"</td> <td>25</td> <td> ✓ </td> <td></td>	1"	25	 ✓ 						
1 3/4" 45 V V V	1 1/4"	32		 ✓ 					
	1 1/2"			 ✓ 	Amazan Salah S				
		45			 ✓ 	 ✓ 	 ✓ 		and the second
	2"	50			 ✓ 	 ✓ 	 ✓ 	 ✓ 	1 Allandaria

Sealumet (Australia) Pty Limited Mailing Address : P0 Box 2218, Warwick, Perth, WA, 6024 Warehouse : Unit 2, 6 Langar Way, Landsdale, Perth, WA - 6065 Telephone : +618 6201 6153, Fax : +618 9303 4560 E-mail: enquiries@sealumet.com Website: www.sealumet.com

DISCLAIMER

These data sheets are based on specifications, data and test results at time of publication. No guarantee as to completeness, accuracy or results is either expressed or implied. The suitability for an intended use is the responsibility of the user. As choice of material, method of application and site conditions are beyond our control we accept no liability for direct or consequential damages. Any material proved to be defective within the published shelf life* will be replaced. *From date of supply.